



INERTWASTE

Transforming inert waste into technosoils for the restoration of mining areas. Restoration of the mine of Eugi (northern Spain).

Iñigo Seminario Errea *MAGNA*

inigo.seminario@magnesitasnav

Mikel Arandigoyen Vidaurre


mikel.arandigoyen@magnesitasnavarras.es

22 MAY 2024 | TLJ2 Slovenia

TLJ2 Slovenia. Restoration of the mine of Eugi

(northern Spain). CONTEXT

- MAGNA is a mining company, leader in the production of magnesium oxide based solutions.
- Located in Navarra (northern Spain), it operates in 45 countries.
- MAGNA has the commitment to restore its mine of Eugi (Navarra).





TLJ2 Slovenia. Restoration of the mine of Eugi

(northern Spain).
KEY ISSUES OF THIS PRACTICE

• WASTE ACCUMULATION:

- Lack of space to store inert waste derived from MAGNA's manufacturing process.
- > 21.707 m³ sludges/year.

SCARCITY OF SOIL FOR RESTORATION:

- High demand of topsoil: > 10.000 m³/season.
- Lack of extraction sites.
- High transport costs: 40 km per truck journey.
- Poor soil quality: cold, from deep





TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain). SOLUTION FOR THE KEY ISSUES

 Using the inert waste generated by the factory to create technosoils for the restoration of the mine.

- "Technosoil": engineered soil created for land improvement, made using a mix of organic and inorganic materials.
- A pilot project was conducted in 2019-2024.



TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain). PILOT PROJECT

Total cost: 667.753€

Public funding: 12%







Regional

National

TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain).

PILOT PROJECT: DESIGN OF THE TECHNOSOIL MIXTURE

- 5 technosoil mixtures were prepared + control soil.
- Mixtures were designed to achieve a loam soil texture.
- All the inert waste used came from MAGNA.
- Organic matter was introduced for soil fertility enhancement.


MAGNA				Technosoi	Technosoi	Technosoi	Technosoi	Technosoi	Control	
	materials		% in the mix		l 1	12	13	14	15	soil
	(all inert,		Inorgani c waste	Sand 1-4 mm	20	20	30	20	20	mine
	without contaminants			Sand 4-12 mm	20	20	0	20	20	
	nor heavy			Sulfamag	0	0	15	0	0	the I
	metals)		(INERT)	Sludge	30	35	30	35	30	
	Nearby organic matter input			Flotation tailings	15	15	15	15	15	soil of
	Phosphorus			Peat	0	0	0	5	0	<u>a</u>
	supply		Organic	Compost	15	10	10	5	10	Natur
			waste	Manure	0	0	0	0	5	Z
				C+ :+	0.4	0.4	0.4	0.4	0.4	

TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain).

PILOT PROJECT: GREENHOUSE AND LABORATORY TRIALS

- Soil samples taken every 15 days during one year.
- Technosoils #1 and #5 were selected as best options due to high nutrient availability, rapid surface coverage, good height growth, and correct pH/conductivity.





Technos oil	Sand	Clay	Silt	Texture	Ph	CE	O.M. %
1	31	9.6	59.4	silty-loam	8.24	446	1.2
2	36.9	17.8	45.3	loam	8.66	171.7	1.05
3	61	25.4	13.6	silty-clay- loam	9.4	2490	0.9
4	30	12.6	57.4	silty-loam	9.11	566.5	1.01
5	38.6	4.8	56.6	silty-loam	8.44	233.9	2.01
Control soil	82	2.4	15.6	sandy	7.3 1	1585 cam r	1 ³ 07_

TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain). PILOT PROJECT: FIELD TEST


- Field tests were carried out with technosoils #1 and #5.
- The mixture was prepared on a larger scale and spread in various locations.
- Under outdoor conditions, technosoil #5 showed the highest cover and herbaceous growth, due to the manure content. Similar properties or











TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain).

PILOT PROJECT: OTHER TECHNOSOIL APPLICATIONS

- Additional tests were carried out to evaluate the potential of technosoils for recreating natural grassland.
- Technosoils achieved good vegetation cover and similar species diversity compared to other soils.





TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain). CONCLUSIONS AND NEXT STEPS

- Technosoils help to convert waste into a resource, and have shown to be viable for landscape restoration.
- Technosoils created from MAGNA's inert waste address the issues of storage limitations and the scarcity of soil in the market.
- MAGNA plans to scale-up the use of technosoils in the restoration of entire slopes.
- The Government of Navarra will use this practice to improve the ERDF within the INERTWASTE project.



TLJ2 Slovenia. Restoration of the mine of Eugi (northern Spain). MAIN CHALLENGES

- Scalability: scaling up the production of technosoils to integrate large-scale projects in the production system of MAGNA.
- Cost and logistics: producing, transporting, applying technosoils at large scales may require significant investments in infrastructure and equipment.
- Designing appropriate mixtures: creating technosoils with the necessary physical, chemical, and biological properties for vegetation growth requires a deep







Thank you ¡Gracias! Eskerrik asko!

www.interregeurope.eu/INERTWASTE